

**TECHNICAL DATA:**

Number of cells along:	<b>10</b>
Lenght of Cables (cm):	<b>120</b>
Number of cells across:	<b>6</b>
Power Rating Pmax (Wp):	<b>370</b>
Power Tolerance:	<b>+5 Wp</b>
Cell width (mm):	<b>166,000</b>
Nominal Voltage Umpp (V):	<b>34,86</b>
Cell length (mm):	<b>166,000</b>
Nominal Current Impp (A):	<b>10,62</b>
Max system voltage (V):	<b>1500</b>
Cell Type:	<b>monocrystalline</b>
Short Circuit Current Isc (A):	<b>11,18</b>
Bifacial:	<b>yes</b>
Connector Type:	<b>MC4 connectable</b>
Open Circuit Voltage Uoc (V):	<b>40,50</b>
Temperature Coefficient Isc (%/K):	<b>0,0400</b>
Frametype:	<b>standard</b>
Temperature Coefficient Pmpp (%/K):	<b>-0,4700</b>
Temperature Coefficient Uoc (%/K):	<b>-0,3500</b>

**ARTICLE DETAILS:**

Manufacturer:	<b>Solitek</b>
Manufacturer Item Name:	<b>BLACKSTAR SOLID framed Glass 60cell Bifacial 370W</b>
Certificate 1:	<b>IEC/TÜV</b>
Certificate 2:	<b>Protection Class 2</b>
Intrastat Product number:	<b>85414300</b>
Frame Color:	<b>black</b>
Backsheet Color:	<b>black</b>
Manufacturer part number: :	<b>BLACKSTAR SOLID FRAMED GLASS/GLASS 370W</b>

**PACKAGING:**

Amount per Pallet:	<b>30</b>
Amount Pal. p. Cont.:	<b>28</b>
Amount per Container:	<b>840</b>

**DIMENSIONS:**

Height (mm):	<b>35</b>
Length (mm):	<b>1782</b>
Weight (kg):	<b>24,000</b>
Width (mm):	<b>1061</b>

**WARRANTY:**

Performance Warranty (yr):	<b>30</b>
Warranter:	<b>Solitek</b>
Product Warranty (yr):	<b>30</b>